

# NGSME9AVB

## 9-PORT AVB POE+ SWITCH

The EASY option for AVB



Niveo Professional introduces the brand new NGSME9AVB switch, offering a ready -out of the box- AVB switch that also supports Dante and PoE+. The switch requires no configuration or difficult firmware uploads, nor any payment or activation of AVB license fees.

- Just unbox, plug-in and relax.
- The switch can be expanded to an 18-port design with a simple expansion cable.
- With a simple command, you can add or remove ports to the Dante-VLAN or the AVB-VLAN.
- The industrial design and specifications, make this the most durable AVB-switch on the market.

More Information at:  
[contact@qtechdistribution.com](mailto:contact@qtechdistribution.com)  
[www.qtechdistribution.com](http://www.qtechdistribution.com)

THE EASY SOLUTION FOR  
AVB & DANTE & POE+  
ON THE SAME SWITCH

-  
DESIGNED &  
MANUFACTURED IN  
GERMANY

-  
EXPANDABLE TO  
16 AVB-PORTS

-  
AVB READY OUT OF  
THE BOX

-  
NO CONFIGURATION OR  
FIRMWARE UPLOADS  
REQUIRED

**AVBU**<sup>®</sup>  
CERTIFIED\*

# NGSME9AVB

## 9-PORT AVB POE+ SWITCH

The EASY option for AVB



GENERAL	ENVIRONMENT & DIMENSIONS
9 * Gigabit Ethernet Ports	High-performance security offload engine including IPSec, SSL, DTLS, and IKE
1- 8 ports for AVB/ 1-8 ports for Dante (user defined)	Hardware compliance with ARM Trustzone® architecture for DRM
1 x SFP 2500BASE-X rear connector for expanding to 16 ports AVB	FIPS-140 certified
4 x 802.3at PoE+ (up to 30W/port)	Dimensions : 160mm (W) x 35mm (H) x 146mm (D)
PoE+ support up to 120W in total	AVNU® MILAN® Bridge Certified
High performance, non-blocking, Gigabit Ethernet	48VDC/54VDC power input operation (135W)
Support for up to 16K MAC addresses, 10KByte Jumbo Frames	RoHS compliant
Supports 802.1 Audio Video Bridging (AVB) Gen 2*	Operating temperature -40°C to +85°C (industrial temperature range)
Time Sensitive Networking (TSN) Standards*, IEEE 1588v2 one-step PTP	Storage temperature -40°C to +85°C, max. gradient 5°C/min
Synchronous Ethernet*	Humidity 5% ... 95% RH non condensing
Quality of Service (QoS) support with 8 traffic classes	Altitude -300m ... +3000m
Supports 4096 802.1Q VLANs, three levels of 802.1Q security	Shock 15g 0.33ms, 6g 6ms
DDR4 2400 1GB, high-speed DRAM memory controller	Vibration 1g 5-2000Hz
eMMC 5.1 Flash 16GB (up to 64GB)	EC Regulatory EN55024, EN55032, EN62368-1 (CE)
SPI Flash 64Mb	FCC
Protected against reverse polarity	MTBF 68.6 years
ESD protection (TVS)	Designed & manufactured in Germany
	3-years warranty