



niveo
P R O F E S S I O N A L



NGS16MCR

(16-slot Media Converter Chassis for Redundant Power Supply)

More information:

WWW.QTECHDISTRIBUTION.COM

CONTACT@QTECHDISTRIBUTION.COM



Key Features

- Up to 16 slots of Media Converters
- 19” standard rack-mount size and 3U height
- Hot-swappable replacement of Media Converters and power supplies
- Two redundant power supplies with two cooling fans
- Power isolation design to ensure each bay is electrically isolated from others

Specifications

| | |
|---|---|
| Capacity | 16 bays for up to 16 Media Converters |
| Power | One hot-swappable power supply Optional second hot-swappable power supply Input: 48V DC |
| Cooling | Two internal cooling fans |
| Dimensions | 130 x 440 x 300 mm (H x W x D) |
| Operating Temperature | 0 to 40°C |
| Storage Temperature | -20 to 90°C |
| Humidity | 10 to 90% RH (non-condensing) |
| Certifications | FCC Class B, CE |
| NGS16MCR-PS, Input 48V DC Media Converter Chassis Power Supply | |
| Dimensions | 90 x 150 x 180 mm (H x W x D) |
| Operating Temperature | 0 to 50°C |
| Storage Temperature | -20 to 70°C |
| Humidity | 10 to 90% RH (non-condensing) |
| Certifications | FCC Class B, CE |